



**TEGERA® 457**



[Learn more](#)

**BIO-CIRCULAR WITH LESS CARBON FOOTPRINT**

Soft and versatile cut protection glove, level C/ANSI cut A3. 13 gg knitted liner including 55% bio-circular Dyneema® fiber and 20% recycled polyester - an innovation that reduces dependence on fossil raw materials. New nitrile foam dipping with reduced usage of water. Touchscreen functionality.

**CHARACTERISTICS**

- Good fingertip sensitivity
- Flexible
- Durable
- Good grip
- Comfortable

**FUNCTIONS**

- Withstands contact heat up to 100°C
- For touchscreen



**PREVENTS RISK OF**

Cut injuries, Scratches, lacerations, Contact with dirt

**PRIMARY ENVIRONMENTS OF USE**

Cut risk environments, Dry environments, Moist environments, Dirty environments

**PRIMARY AREAS OF USE**

Airport work, Assembly, Building and construction, Fine assembly, Inspection work, Machine operating, Warehouse work

**PRIMARY INDUSTRIES OF USE**

Agriculture, forestry and fishing, Automotive manufacturing, Basic metals manufacturing, Building and construction, Electricity and gas supply, Machinery and equipment manufacturing, Metal manufacturing and fabrication, Mining and quarrying, Pulp and paper, Transportation and logistics, Warehousing

**TYPE OF WORK**

Light weight

**SPECIFICATION**

**TYPE** Cut resistant gloves, Heat protection gloves

**CATEGORY** Cat. II

**KNITTING GAUGE (GG)** 13

**LINING MATERIAL** Dyneema® fiber from bio-circular feedstock, Glass fibre thread, Recycled polyester, Spandex

**LENGTH** 225-275 mm

**DEXTERITY** 5

**GRIP DESIGN** Foam grip pattern

**COLOUR** Green

**PAIRS PER: BUNDLE/CARTON** 6/120

**DISPLAY TYPE** Bulk pack

**DIPPING** Palm-dipped

**DIPPING MATERIAL** Nitrile foam, Waterbased PU

**CUFF STYLE** Knitwrist cuff

**CUFF MATERIAL** Textile

**CUT RESISTANCE (EN ISO 13997)** Cut resistance level C

**CUT RESISTANCE (EN ISO 13997) TDM:** 10.9 N

**INNER MATERIAL SPECIFICATION** UHMWPE (Ultra high molecular weight polyethylene), Glass fibre thread, Recycled polyester, Elastane

**OUTER MATERIAL SPECIFICATION** Nitrile



**COMPLIANCE**



EN ISO 21420:2020



TP TC 019:2011



Contact heat rating valid for palm area only

**FEATURES**



| SIZE |     | ARTICLE NUMBER | EAN           |
|------|-----|----------------|---------------|
| 6    | XS  | 457-6          | 7340118430973 |
| 7    | S   | 457-7          | 7340118431123 |
| 8    | M   | 457-8          | 7340118431277 |
| 9    | L   | 457-9          | 7340118431420 |
| 10   | XL  | 457-10         | 7340118431574 |
| 11   | XXL | 457-11         | 7340118431727 |

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden  
 Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com